


STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **BOBCAT**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	66	9	29	195		V	40-10	135TA5185
	2	66	9	29,3	208			40-10	135TA5404
	2	73,7	12	37	240			40-10	135TA5432
	2	74	9	29	215			45-10	135TA5398
	2	74	13	38	248		V	45-10	135TA5303
	2	77	13	41	240		V	55-25	136TA3491
	2	82,5	9	34	210		V	40-10	135TA5316
	2	82,5	13	46,5	292			35-05	135TA5580
	2	89	10	40	220		V	40-10	135TA5102
	2	95	9	32	285			40-10	135TA5167
	2	95	10	39,6	235		V	40-10	135TA5469
	3	88,5	9	29	305	V		35-55-10	135TA5276




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **BOBCAT**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,5	10	36,5	309			45-60-15	135TA5476
	3	88,5	10	38	341	V		40-55-05	103TA3475
	3	88,5	10	39,8	317		V	40-55-10	135TA5470
	3	88,5	10	40	290		V	40-55-10	136TA3458
	3	88,5	12	46	341		V	55-10-25	135TA5382
	3	89	10	32	340		V	55-05-20	136TA3493
	3	89	10	39,7	341	V	V	35-50-05	135TA5557
	3	89	11	40	296	V	V	50-10-25	135TA5564
	3	89	12	46	342		V	55-10-25	135TA5329
	3	92	10	39	308			50-10-25	135TA5348

