


STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **COVENTRY CLIMAX**



voltage (volt)	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	77	8	28	183			40-10	119TA7501
	2	82	8	28	190			40-10	105TA5086
	2	95	9	32	210		V	40-10	105TA5092
	2	95	9	32	230		V	40-10	135TA5166
	2	95	9	32	305			40-10	105TA5091
	3	0	11	28,5	237	V		40-50-05	106TA8392
	3	65	12	32	222			35-50-05	103TA3578
	3	74	9	29	210		V	40-50-10	105TA5093
	3	74	9	29	230		V	40-50-10	105TA5085
	3	88,5	9	29	305			30-45-60	124TA6068
	3	88,5	9	29	305	V		40-55-10	105TA5084
	3	88,7	10	39,5	309,2			40-55-10	124TA6164




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **COVENTRY CLIMAX**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	89	10	39	310			50-10-20	105TA5087
	3	89	10	39	360			40-55-10	105TA5083
	3	92	9	36	310	V		40-55-10	135TA5578
24	3	88,5	10	39	365	V		40-55-05	119TA7509

