



used for DAEWOO				
TRACK ROLLER	TOP ROLLER	SPROCKET	IDLER	TRACK
				
<b>DAEWOO SOLAR015</b>				
<b>REF 144TA7880</b> (Ø flange = 98,00 mm) (Ø body = 80,00 mm)		<b>REF 163TA9158</b>	<b>REF 143TA9332</b> (front, with bracket assembly)	<b>REF 164TA9692</b> (rubber) (230 x 96 x 33)
<b>DAEWOO SOLAR015-Plus</b>				
<b>REF 143TA8626</b>		<b>REF 144TA7678</b> (number of teeth = 19) (number of holes = 9)	<b>REF 143TA9332</b> (front, with bracket assembly)	<b>REF 164TA9692</b> (rubber) (230 x 96 x 33)
<b>DAEWOO SOLAR030</b>				
<b>REF 163TA9791</b> (for steel tracks)		<b>REF 144TA7679</b> (number of teeth = 21) (number of holes = 12)	<b>REF 144TA7592</b> (front, with bracket assembly) (Ø = 311,00 mm)	<b>REF 143TA9698</b> (rubber) (300 x 52,5 x 76)
<b>REF 144TA7881</b> (Ø flange = 133,00 mm) (Ø body = 95,00 mm)			<b>REF 163TA9810</b> (front, with bracket assembly) (for steel tracks)	
<b>DAEWOO SOLAR030-Plus</b>				
<b>REF 144TA7882</b> (Ø flange = 133,00 mm) (Ø body = 95,00 mm)		<b>REF 144TA7680</b> (number of teeth = 21) (number of holes = 12)	<b>REF 144TA7593</b> (front, with bracket assembly) (Ø = 311,00 mm)	<b>REF 143TA9698</b> (rubber) (300 x 52,5 x 76)
<b>DAEWOO SOLAR035</b>				
<b>REF 144TA7884</b> (for steel tracks) (Ø flange = 115,00 mm) (Ø body = 95,00 mm)		<b>REF 144TA7681</b> (number of teeth = 21) (number of holes = 12)	<b>REF 144TA7594</b> (front, with bracket assembly) (Ø = 311,00 mm)	<b>REF 143TA9699</b> (rubber) (300 x 52,5 x 84)
<b>REF 144TA7883</b> (Ø flange = 133,00 mm) (Ø body = 95,00 mm)			<b>REF 163TA9810</b> (front, with bracket assembly) (for steel tracks)	
<b>DAEWOO SOLAR50</b>				
<b>REF 144TA7885</b>			<b>REF 144TA7595</b> (front, with bracket assembly) (Ø = 385,00 mm)	
<b>DAEWOO SOLAR55</b>				
<b>REF 144TA7886</b> (Ø flange = 128,00 mm) (Ø body = 94,00 mm)	<b>REF 144TA7760</b> (assembly) (Ø flange = 128,00 mm) (Ø body = 94,00 mm)	<b>REF 144TA7682</b> (number of teeth = 19) (number of holes = 9)	<b>REF 144TA7596</b> (front, with bracket assembly)	<b>REF 143TA9701</b> (rubber) (400 x 72,5 x 74)
<b>DAEWOO SOLAR55V-Plus</b>				
<b>REF 144TA7887</b> (Ø flange = 128,00 mm) (Ø body = 94,00 mm)	<b>REF 144TA7761</b> (assembly) (Ø flange = 128,00 mm) (Ø body = 94,00 mm)	<b>REF 144TA7683</b> (number of holes = 12)	<b>REF 144TA7597</b> (front, with bracket assembly)	<b>REF 143TA9701</b> (rubber) (400 x 72,5 x 74)
<b>DAEWOO SOLAR70-III</b>				
<b>REF 163TA9793</b> (for rubber tracks)	<b>REF 163TA9257</b> (assembly) (Ø body = 100,00 mm)	<b>REF 163TA9787</b> (number of teeth = 21) (number of holes = 12)	<b>REF 143TA9291</b> (front, with bracket assembly)	<b>REF 143TA9696</b> (rubber) (450 x 81 x 74)
<b>REF 163TA9794</b> (for steel tracks)				