


STARTERS

For all our latest catalogue updates and company info: www.tvh.com



STARTERS

used for: **FENWICK & PEG**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	2	82	9	25	293				106TA8261
	2	82	9	29	280			50-20	105TA5103
	2	82	9	34	295			55-25	107TA9575
	2	82	9	36,5	291,5			50-20	106TA8259
	2	82,5	9	30	291			55-25	103TA3541
	3	65	10	27	262			40-55-05	135TA5400
	3	66	9	25	195			55-10-25	103TA3163
	3	82	9	25	265			35-05-20	105TA5107
	3	82	11	29	225			35-50-05	135TA5128
	3	82,5	9	25	225			35-05-20	105TA5106
	3	88,4	10	39,2	306	V		50-10-20	135TA5510
	3	88,5	9	29	305	V		40-55-10	105TA5108




STARTERS

For all our latest catalogue updates and company info: www.tvh.com

STARTERS

used for: **FENWICK & PEG**



voltage (volt) U	number of fixation points AT-BG	flange dia. (mm) D1	number of teeth AT-TA	gear dia. (mm) D2	total length (mm) L	wet clutch OLIED	reductor TY-ST	position fixation points LG-BG	reference new
12	3	88,5	9	34	295			50-05-20	124TA6177
	3	88,5	9	34	295			35-50-05	135TA5192
	3	88,5	10	26	220			35-50-05	103TA3169
	3	88,5	10	40	295			55-10-20	103TA3367
	3	88,5	10	40	315			55-10-20	105TA5110
	3	88,5	10	40	325			50-10-20	103TA3168
	3	89	10	39	310			50-10-20	135TA5600
	3	89	10	39	360			40-55-10	105TA5104
	3	110	9	34	340			35-50-05	116TA7101
24	3	88,5	9	34	415			35-55-05	106TA8270
	3	88,8	10	39	340			35-55-05	135TA5591

